

View Online at <https://aerobasegroup.com/nsn/5905-00-642-5020>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.875 inches

First Flat Length:

0.344 inches

Flat Height:

0.031 inches

Body Diameter:

4.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

2.000 inches

Overall Diameter:

4.281 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Fragility Factor:

Moderately delicate

Screw Thread Diameter:

0.375 inches and 0.190 inches

Screw Thread Series Designator:

Unef and unef

Screw Thready Qty Per Inch (tpi):

32.0 and 32.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

8.000 ohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

150.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

64959-ba10027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0