## NSN 5905-00-642-5150

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-642-5150 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.157 inches **Body Diameter:** 1.562 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.375 inches **Overall Diameter:** 1.719 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing

**Electrical Resistance Per Section:** 

1.000 ohms single section

**Power Dissipation Rating Per Section In Watts:** 

25.0 free air single section

## NSN 5905-00-642-5150

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	<b>Tolerance</b>	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0