NSN 5905-00-643-5707

Section Quantity:

0.00800 inches

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-643-5707

Section Quantity.
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 2.771 inches and 2.853 inches
Terminal Length:
Between 0.203 inches and 0.235 inches
Body Diameter:
Between 1.796 inches and 1.828 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.735 inches and 0.765 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
Between 1.990 inches and 2.010 inches
Overall Diameter:
Between 1.999 inches and 2.063 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.75 inch-ounces
Maximum Running Torque:
1.25 inch-ounces
Maximum Stop Torque:
750.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.557 inches and 0.567 inches
Shaft End Play:

NSN 5905-00-643-5707

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.002 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Upper adjacent side two rows
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
110.0 single section
Power Dissipation Rating Per Section In Watts:
8.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-643-5707

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0