Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-643-6483

view chilling at https://doi/obdobgioup.com/holi/ob
Section Quantity:
1
First Flat Length:
2.000 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.500 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
1.094 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.000 kilohms single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0