

View Online at <https://aerobasegroup.com/nsn/5905-00-643-7344>

Section Quantity:

2

Body Style:

Cylindrical studs mounted

Reliability Indicator:

Not established

Overall Length:

2.312 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Body Length:

1.938 inches

Overall Diameter:

2.093 inches

Mounting Hole/stud Circle Diameter:

0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

325.0 and 305.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Screw Thread Diameter:

0.138 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

325.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 2nd section

Power Dissipation Rating Per Section In Watts:

2.5 free air all sections

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0