NSN 5905-00-643-9954

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-643-9954 **Section Quantity: Body Style:** Cylindrical studs mounted **Reliability Indicator:** Not established **Overall Length:** 1.141 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Body Length:** 1.250 inches **Overall Diameter:** 1.820 inches **Mounting Hole/stud Circle Diameter:** 1.203 inches 1080.0

Shaft Style: Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 3 **Terminal Location:**

Lower adjacent side single row

Mounting Method: Threaded hole

NSN 5905-00-643-9954

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
10.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
1080.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Power Dissipation Rating Per Section In Watts:	
5.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A002a0	