NSN 5905-00-644-6712

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-644-6712

| Section Quantity: |
|---|
| 1 |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.375 inches |
| Shaft Style: |
| Round |
| Switch Type: |
| Rotary |
| Switch Voltage Rating In Volts: |
| 120.0 |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Switch Operating Position: |
| Start of rotation |
| Switch Contact Arrangement: |
| Single pole, single throw, normally open, both positions maintained |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Switch |
| Electrical Resistance Per Section: |
| 5.000 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -20.0/+20.0 single section |
| Switch Current Type And Rating In Amps: |

3.000 ac/dc

NSN 5905-00-644-6712

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 5 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0