Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-644-6797

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

2.332 inches

#### **Body Diameter:**

1.680 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

#### Shaft Length:

Between 0.828 inches and 0.922 inches

#### Mounting Bushing Length:

Between 0.328 inches and 0.422 inches

**Body Length:** 

1.410 inches

#### **Overall Diameter:**

2.260 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

#### Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Standard bushing

# NSN 5905-00-644-6797

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



# Electrical Resistance Per Section:

250.000 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

Between 275.0 and 305.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

**Power Dissipation Rating Per Section In Watts:** 

25.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## **Actuator Travel Control Feature:**

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

**Standard Taper Curve Per Section:** 

A single section

#### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-22/3 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0