## NSN 5905-00-644-6850

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-644-6850

Section Quantity:					
1					
Body Style:					
Cylindrical bushing mounted					
Reliability Indicator:					
Not established					
Body Diameter:					
1.250 inches					
Shaft Diameter:					
0.250 inches					
Shaft Length:					
0.250 inches					
Mounting Bushing Length:					
0.500 inches					
Body Length:					
0.625 inches					
Shaft Style:					
Round, slotted					
Actuator Type:					
Single shaft					
Nonturn Device Location:					
Nonturn Device Location: At 9 oclock					
At 9 oclock					
At 9 oclock  Nonturn Device Radius:					
At 9 oclock  Nonturn Device Radius:  0.531 inches					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method: Locking bushing					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Locking bushing  Electrical Resistance Per Section:					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Locking bushing  Electrical Resistance Per Section:  1.000 kilohms single section					
At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Locking bushing  Electrical Resistance Per Section:  1.000 kilohms single section  Power Dissipation Rating Per Section In Watts:					

A single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-644-6850

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Termi	nal	Тур	And	Quar	itity:
3 tab,	sol	der lu	Jg		

o tab, solder la

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0