NSN 5905-00-644-8532

No

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-644-8532

Townselves Coefficient Of Bosistanos In Boso Bos Colsins
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
190.000 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.320 inches and 0.440 inches
Body Diameter:
Between 0.660 inches and 0.840 inches
Body Length:
Between 0.780 inches and 1.100 inches
Power Dissipation Rating In Watts:
0.400 free air
Terminal Width:
0.016 inches
Cubic Measure (non-core):
0.415 cubic inches
Style Designator:
Axial terminals one end
Test Data Document:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-93/7 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

NSN 5905-00-644-8532

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0