## NSN 5905-00-646-5921

Inductive Wire Wound Fixed Resistor - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5905-00-646-5921
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/ <b>+</b> 260.0
Electrical Resistance:
120.000 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.406 inches and 0.468 inches
Body Length:
Between 2.719 inches and 2.781 inches
Body Width:
1.187 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.938 inches and 2.062 inches
Power Dissipation Rating In Watts:
31.000 free air
Terminal Width:
Between 0.172 inches and 0.265 inches
Mounting Hole Size:
Between 0.146 inches and 0.246 inches
Style Designator:
Terminals one edge
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/2 government specification
Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5905-00-646-5921

Inductive Wire Wound Fixed Resistor - Page 2 of 2



em			

No

Fiig:

A001a0