

NSN 5905-00-646-7155 Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-646-7155 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.344 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches

Mounting Bushing Length: 0.500 inches **Body Length:**

0.469 inches **Shaft Style:** Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Nonturn Device Location:

At 10 oclock

Nonturn Device Radius:

0.250 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Locking bushing w/shaft seal

Features Provided:

Shaft locking device

Electrical Resistance Per Section:

28.000 megohms single section

NSN 5905-00-646-7155

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: