Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-650-1673

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

3.000 inches

#### Shaft Diameter:

0.312 inches

#### Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.250 inches

#### Body Length:

## 1.156 inches

Shaft Style:

#### Round

Actuator Type:

## Single shaft

End Application:

Forrestal class cv

## Screw Thread Diameter:

0.138 inches

#### Screw Thread Series Designator:

Unc

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

100.000 kilohms single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

8.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0