

View Online at <https://aerobasegroup.com/nsn/5905-00-651-1618>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.3120 inches and 1.3125 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.3125 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.453 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

Between 0.656 inches and 0.719 inches

Body Length:

1.580 inches

Mounting Lip Diameter:

1.4380 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

345.0

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

43.900 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0