

View Online at <https://aerobasegroup.com/nsn/5905-00-651-1621>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.3115 inches and 1.3120 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.312 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.453 inches

**Shaft Diameter:**

Between 0.2494 inches and 0.2497 inches

**Shaft Length:**

1.884 inches

**Body Length:**

1.040 inches

**Overall Diameter:**

1.453 inches

**Mounting Lip Diameter:**

1.4380 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Contact Arm Electrical Off Position:**

Fully ccw-cw

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

349.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

43.900 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0