## NSN 5905-00-651-1632

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-651-1632 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3120 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 1.453 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.688 inches **Body Length:** 2.120 inches **Mounting Lip Diameter:** 1.4380 inches **Mounting Lip Depth:** 0.0630 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** 

Bearing **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 349.0 **Maximum Starting Torque:** 2.20 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches



NSN 5905-00-651-1632 Precision Wire Wound Variable Resistor - Page 2 of 3	AeroBase Group
Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.00100 inches	
Shaft Radial Play:	
0.0015 inches	
Mechanical Backlash In Deg Angular Rotation:	
10.0	
Terminal Location:	

Radially positioned over more than half the circumference

**Mounting Method:** 

Clamp ring

**Electrical Resistance Per Section:** 

50.000 percent, rated amperes c and better industrial clears

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

172.0 all sections

**Rotary Actuator Travel In Angular Deg:** 

360.0

**Function Conformity Tolerance Per Section:** 

-1.50/+1.50 3rd section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air all sections

**Function Conformity Per Section:** 

1st section absolute linearity

**Fixed Tap Quantity Per Section:** 

1 all sections

**Tap Location Tolerance Per Section:** 

-1.0/+1.0 degrees angular rotation all sections

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 3rd section

**Actuator Travel Control Feature:** 

Continuous motion

**Function Characteristic Per Section:** 

9 oclock all primaries

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

**Terminal Type And Quantity:** 

12 turret

Shelf Life:

N/a

## NSN 5905-00-651-1632

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0