

View Online at <https://aerobasegroup.com/nsn/5905-00-651-1640>

**Section Quantity:**

5

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.3115 inches and 1.3120 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

3.879 inches

**Undercut Diameter:**

1.312 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.453 inches

**Shaft Diameter:**

Between 0.249 inches and 0.250 inches

**Shaft Length:**

Between 0.657 inches and 0.719 inches

**Body Length:**

3.160 inches

**Overall Diameter:**

1.706 inches

**Mounting Lip Diameter:**

1.4380 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

345.0

**Maximum Starting Torque:**

3.40 inch-ounces

**Maximum Running Torque:**

2.40 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

9.750 percent, rated amperes c and better v.G. Stepping

**Rotary Actuator Travel In Angular Deg:**

349.0

**Function Conformity Tolerance Per Section:**

-0.65/+0.65 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 5th section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

15 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0