## NSN 5905-00-651-1648

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-651-1648 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3120 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.422 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.688 inches **Body Length:** 2.660 inches **Mounting Lip Diameter:** 1.4380 inches **Mounting Lip Depth:** 0.0730 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 2.80 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Shaft End Play:** 0.00500 inches

**Shaft Runout:** 0.002 inches

### NSN 5905-00-651-1648



Precision Wire Wound Variable Resistor - Page 2 of 3	
Lateral Runout:	
0.002 inches	
Pilot Diameter Runout:	
0.00200 inches	
Shaft Radial Play:	
0.002 inches	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Features Provided:	
Humidity proof	
Electrical Resistance Per Section:	
28.605 percent, rated amperes c and better select	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-1.00/+1.00 all sections	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 all sections	
Power Dissipation Rating Per Section In Watts:	
2.0 free air all sections	
Function Conformity Per Section:	
All sections absolute conformity	
Fixed Tap Quantity Per Section:	
3 3rd section	
Tap Location Tolerance Per Section:	
-1.0/+1.0 ohms all sections	
Resistance Tolerance Per Section In Percent	

#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

#### **Actuator Travel Control Feature:**

Continuous motion

#### **Tap Location From Ccw Terminal Per Section In Ohms:**

727.0 3rd section and 10000.0 3rd section and 17878.0 3rd section

#### **Function Characteristic Per Section:**

All sections 360 degrees sine-cosine

#### Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

#### **Terminal Type And Quantity:**

17 turret

#### Shelf Life:

N/a

# NSN 5905-00-651-1648

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0