NSN 5905-00-651-1649

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-651-1649 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.580 inches **Undercut Diameter:** 1.422 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.687 inches **Body Length:** 1.366 inches **Overall Diameter:** 1.437 inches **Mounting Lip Diameter:** 1.4530 inches **Mounting Lip Depth:** 0.0730 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 349.0 **Maximum Starting Torque:**

1.60 inch-ounces

Maximum Running Torque:

1.10 inch-ounces

NSN 5905-00-651-1649

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.01000 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.005 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
25.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
Power Dissipation Rating Per Section In Watts: 2.0 free air all sections
2.0 free air all sections
2.0 free air all sections Function Conformity Per Section:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Precious Material And Location:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Precious Material And Location: Terminals gold
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Precious Material And Location: Terminals gold Precious Material:
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Precious Material And Location: Terminals gold Precious Material: Gold
2.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity:

NSN 5905-00-651-1649

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0