## NSN 5905-00-651-1672

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-651-1672

Section Quantity:

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical servo mounted   |
| Reliability Indicator:  |
| Not established   |
| Pilot Diameter:   |
| Between 1.5610 inches and 1.5620 inches   |
| Pilot Length:   |
| 0.0620 inches   |
| Undercut Diameter:  |
| 1.562 inches  |
| Undercut Width:   |
| 0.0730 inches   |
| Body Diameter:  |
| 1.750 inches  |
| Shaft Diameter:   |
| 0.2497 inches   |
| Shaft Length:   |
| 0.561 inches  |
| Body Length:  |
| 0.880 inches  |
| Overall Diameter:   |
| 1.938 inches  |
| Mounting Lip Diameter:  |
| 1.7500 inches   |
|   |
| Mounting Lip Depth:   |
| Mounting Lip Depth: 0.0930 inches   |
|   |
| 0.0930 inches   |
| 0.0930 inches Shaft Style:  |
| 0.0930 inches Shaft Style: Round  |
| 0.0930 inches  Shaft Style:  Round  Shaft Bearing Type:   |
| 0.0930 inches Shaft Style: Round Shaft Bearing Type: Ball   |
| 0.0930 inches Shaft Style: Round Shaft Bearing Type: Ball Actuator Type:  |
| 0.0930 inches  Shaft Style:  Round  Shaft Bearing Type:  Ball  Actuator Type:  Double ended shaft   |
| 0.0930 inches Shaft Style: Round Shaft Bearing Type: Ball Actuator Type: Double ended shaft Effective Electrical Rotation In Deg Angular Rotation:                                |
| 0.0930 inches Shaft Style: Round Shaft Bearing Type: Ball Actuator Type: Double ended shaft Effective Electrical Rotation In Deg Angular Rotation: 354.0                          |
| 0.0930 inches Shaft Style: Round Shaft Bearing Type: Ball Actuator Type: Double ended shaft Effective Electrical Rotation In Deg Angular Rotation: 354.0 Maximum Starting Torque: |

Shaft End Play: 0.00500 inches

## NSN 5905-00-651-1672

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Runout:  |
|--|
| 0.002 inches   |
| Lateral Runout:  |
| 0.002 inches   |
| Pilot Diameter Runout:   |
| 0.00200 inches   |
| Shaft Radial Play:   |
| 0.002 inches   |
| Terminal Location:   |
| Radially positioned over less than half the circumference                      |
| Mounting Method:   |
| Clamp ring   |
| Features Provided:   |
| Nonmetallic shaft  |
| Electrical Resistance Per Section:   |
| 25.000 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:   |
| 360.0  |
| Function Conformity Tolerance Per Section:                                     |
| -0.30/+0.30 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:    |
| 105.0 single section   |
| Power Dissipation Rating Per Section In Watts:                                 |
| 3.0 free air single section  |
| Function Conformity Per Section:   |
| Single section independent linearity   |
| Resistance Tolerance Per Section In Percent:                                   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Continuous motion  |
| Function Characteristic Per Section:   |
| Single section linear  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:            |
| 40.0 single section  |
| Precious Material And Location:  |
| Terminals gold   |
| Precious Material:   |
| Gold   |
| Terminal Type And Quantity:  |
| 3 solder stud  |
| Shelf Life:  |
| N/   |

N/a

## NSN 5905-00-651-1672

Precision Wire Wound Variable Resistor - Page 3 of 3



| ın | 1+ | <i>(</i> )+ | Measure | • |
|----|----|-------------|---------|---|
|    |    |             |         |   |

--

Demilitarization:

No

Fiig:

A002a0