

View Online at <https://aerobasegroup.com/nsn/5905-00-651-1675>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

2.8740 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

2.825 inches

**Undercut Width:**

0.0930 inches

**Body Diameter:**

2.875 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.625 inches

**Body Length:**

1.620 inches

**Mounting Lip Diameter:**

3.0000 inches

**Mounting Lip Depth:**

0.0730 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

345.0

**Maximum Starting Torque:**

2.20 inch-ounces

**Maximum Running Torque:**

1.30 inch-ounces

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.0 kilohms all sections

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

172.5 all sections

**Rotary Actuator Travel In Angular Deg:**

345.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

5.0 free air all sections

**Function Conformity Per Section:**

All sections absolute linearity

**Fixed Tap Quantity Per Section:**

2 all sections

**Tap Location Tolerance Per Section:**

-1.0/+1.0 degrees angular rotation all sections

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0