## NSN 5905-00-651-1684

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-651-1684

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
3.250 inches
Terminal Length:
24.000 inches
Overall Height:
0.562 inches
Overall Width:
0.562 inches
Shaft Diameter:
0.190 inches
Shaft Length:
1.500 inches
Mounting Bushing Length:
0.625 inches
Body Length:
1.750 inches
Body Width:
0.562 inches
Body Height:
0.562 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:

1.000 kilohms single section

## NSN 5905-00-651-1684

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watt	s:
--	----

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

**Terminal Type And Quantity:** 

1 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0