Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-655-1088

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### First Flat Length:

0.344 inches

#### Flat Height:

0.219 inches

#### Body Diameter:

3.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

# Mounting Bushing Length:

0.375 inches

### **Body Length:**

1.750 inches

### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 12 oclock

### Nonturn Device Radius:

0.500 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# Terminal Location:

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.000 ohms single section

# Power Dissipation Rating Per Section In Watts:

100.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0