Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-655-3724

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.250 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.062 inches

## Mounting Bushing Length:

0.687 inches

## Body Length:

## 0.620 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

265.0

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.138 inches

#### **Screw Thread Series Designator:**

Unc

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Features Provided:**

Nonmetallic shaft

## **Electrical Resistance Per Section:**

500.000 ohms single section

## Rotary Actuator Travel In Angular Deg:

265.0



# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## **Actuator Travel Control Feature:**

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

## Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0