NSN 5905-00-655-3726

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-655-3726 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 2.750 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 3.250 inches **Mounting Stud Length:** 0.750 inches **Body Length:** 1.125 inches **Mounting Hole/stud Circle Diameter:** 0.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 330.0 **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded stud **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:**

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:
330.0

NSN 5905-00-655-3726

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
10.7 free air single section
Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
100.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: