

View Online at <https://aerobasegroup.com/nsn/5905-00-656-2388>

Section Quantity:

4

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.562 inches

Shaft Diameter:

Between 0.187 inches and 0.265 inches

Shaft Length:

Between 3.843 inches and 4.250 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.250 inches

Undercut Diameter:

0.226 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Undercut Length:

2.023 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.000 kilohms 4th section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air 1st section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 4th section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0