

View Online at <https://aerobasegroup.com/nsn/5905-00-657-1595>

Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.740 inches and 0.760 inches

Mounting Hole Diameter:

Between 0.093 inches and 0.097 inches

Body Length:

Between 0.500 inches and 0.510 inches

Actuator Type:

Integral knob

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

Between 0.958 inches and 0.962 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Humidity proof

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

315.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0