Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-3803

Section Quantity:

1

- Body Style: Cylindrical bushing mounted
- Reliability Indicator:
- Not established
- **Body Diameter:**
- 0.750 inches
- Shaft Diameter:
- 0.125 inches
- Shaft Length:
- 0.500 inches
- Mounting Bushing Length:
- 0.375 inches
- Body Length:
- 0.375 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Nonturn Device Location:
- At 9 oclock
- Nonturn Device Radius:
- 0.375 inches
- Screw Thread Diameter:
- 0.250 inches
- Screw Thread Series Designator:
- Unef
- Screw Thready Qty Per Inch (tpi):
- 32.0
- **Terminal Location:**
- Right adjacent side single row
- **Mounting Method:**
- Standard bushing
- **Electrical Resistance Per Section:**
- 1.000 kilohms single section
- **Power Dissipation Rating Per Section In Watts:**
- 0.5 free air single section
- **Resistance Tolerance Per Section In Percent:**
- -20.0 to 20.0 single section
- Standard Taper Curve Per Section:
- A single section



Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0