Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-3804

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Body Diameter:

0.750 inches

# Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

# Mounting Bushing Length:

0.375 inches

# Body Length:

0.375 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

# **Nonturn Device Location:**

At 9 oclock

# Nonturn Device Radius:

0.375 inches

# Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.000 kilohms single section

# **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Standard Taper Curve Per Section:

A single section

# **Test Data Document:**

81349-milr94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0