NSN 5905-00-660-3994

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-3994

1
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
0.750 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.375 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
250.000 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Switch Current Type And Rating In Amps:
5.000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a

NSN 5905-00-660-3994

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0