## NSN 5905-00-660-4364

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-660-4364

Biochical Resistance:000 megohms Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Immorrance Method: Immorra	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1,000/4-1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Impurature Resident Celsius: 65.0/+145.0 Impurature Method: 65.0/+145.0 Impurature Method: 66.0/+145.0 Impurature Method: 67.0/** 67.0/** 67.0/** 67.0/* 67.0	-30.0/+30.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Tempurature Method: 16.00-psulated Terminal Type: Wire lead Reliability Indicator: 10-00 inches	Electrical Resistance:
1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Incapsulated Terminal Type: Wife lead Reliability Indicator: Not established 30dy Diameter: 1.500 inches 30dy Diameter: 1.500 inches 30dy Length: 1.000 inches 30dy Length: 1.000 inches 30dy Length: 1.000 free air 31dy-milry444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No	1.000 megohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  185.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Rody Diameter:  1.500 inches  Rody Length:  1.000 inches  Power Dissipation Rating In Watts:  1.000 free air  Riyle Designator:  Wait terminal each end  Test Data Document:  181494-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via Joint Of Measure:  Joint Office Advanced And Power Action Actio	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+145.0  Inclosure Method:  Incapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  15.500 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  10.000 ree air  Skyle Designator:  2014 Skyle Designator:  2014 Skyle Designator:  2014 Skyle Test Data Document:  2015 1399-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  2016 Life:  2016 1401 1501 1501 1501 1501 1501 1501 1501	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+145.0  Inclosure Method:  Incapsulated  Ferminal Type:  Wife lead  Reliability Indicator:  Not established  Body Diameter:  1.500 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Avial terminal each end  Fest Data Document:  181349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via Juit Of Measure:  - Demilitarization:  No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Rempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Reminal Type: Wife lead Reliability Indicator: Not established Rody Diameter: 1.500 inches Rody	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 9.500 inches Body Diameter: 9.500 inches Power Dissipation Rating In Watts: 9.000 free air Style Designator: Rival terminal each end Test Data Document: 81349-miltip444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 9xxcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: 1/4a Juit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
actions and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via Gesaure:  Joni Of Measure:  Jo	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 1.500 inches 30dy Length: 1.000 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Xival terminal each end Fest Data Document: 11349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Via Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 0.000 free air Skyle Designator: Valid terminal each end Fest Data Document: 101349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Value Unit Of Measure: - Demilitarization: No	-65.0/+145.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  D.500 inches  Body Length:  D.000 inches  Power Dissipation Rating In Watts:  Reliability Designator:  Exist Leminal each end  Fest Data Document:  B1349-millr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Va  Joit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Body Diameter:  0.500 inches  Body Length: 0.000 inches  Power Dissipation Rating In Watts: 0.000 free air  Style Designator: Avial terminal each end  Fest Data Document: 0.1349-millr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Juit Of Measure: - Demilitarization:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: - Demilitarization:	Terminal Type:
Note established  Rody Diameter:  1.500 inches  Rody Length:  1.000 inches  Power Dissipation Rating In Watts:  1.000 free air  Rotyle Designator:  Rotyle Designator:	Wire lead
Body Length:  2.500 inches  Body Length:  2.000 inches  Power Dissipation Rating In Watts:  2.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  2.31349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:	Reliability Indicator:
2.500 inches 2.500	Not established
Body Length:  1.000 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  181349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	0.500 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  31349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jinit Of Measure:  Demilitarization:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.000 inches
Style Designator: Axial terminal each end Fest Data Document: B1349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  31349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.000 free air
Fest Data Document: 81349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Style Designator:
B1349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	81349-milr9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
√a Jnit Of Measure: - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
A001a0	A001a0