

View Online at <https://aerobasegroup.com/nsn/5905-00-660-5254>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.3120 inches and 1.3125 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.312 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.437 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.625 inches

Body Length:

1.540 inches

Mounting Lip Diameter:

Between 1.4320 inches and 1.4420 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.70 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.004 inches

Pilot Diameter Runout:

0.00150 inches

Shaft Radial Play:

0.004 inches

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.65/+0.65 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections absolute linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0