NSN 5905-00-660-5728

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-5728

| Section Quantity: |
|--|
| 2 |
| Body Style: |
| Cylindrical bushing mounted |
| First Flat Length: |
| 0.375 inches |
| Flat Height: |
| 0.095 inches |
| Body Diameter: |
| 0.969 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.875 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.781 inches |
| Shaft Style: |
| Round, flatted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 6 oclock |
| Nonturn Device Radius: |
| 0.281 inches |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 500.000 ohms 1st section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -5.0 to 5.0 all sections |

NSN 5905-00-660-5728

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Function Characteristic Per Section: |
|---|
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| Any acceptable |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |