Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-6560

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## First Flat Length:

0.344 inches

#### Flat Height:

0.188 inches

**Body Diameter:** 

0.906 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

## 0.875 inches

## Mounting Bushing Length:

0.375 inches

#### **Body Length:**

0.375 inches

### Shaft Style:

Round, flatted

## Actuator Type:

Single shaft

## Nonturn Device Location:

At 12 oclock

#### **Nonturn Device Radius:**

0.500 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

1.000 megohms single section

# Power Dissipation Rating Per Section In Watts:

100.0 free air single section



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0