## NSN 5905-00-660-6758

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-6758 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.375 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.438 inches **Overall Diameter:** 1.125 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

1.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

## NSN 5905-00-660-6758

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percen |
|--|
| -20.0 to 20.0 single section               |
| Standard Taper Curve Per Section:          |
| A single section                           |
| Terminal Type And Quantity:                |
| 3 tab, solder lug                          |
| Shelf Life:                                |
| N/a  |
| Unit Of Measure:                           |

**Demilitarization:** No

Fiig:

A002a0