NSN 5905-00-660-9962

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-660-9962

Continue Occupation
Section Quantity:
·
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.313 inches
Terminal Length:
Between 0.484 inches and 0.516 inches
Overall Height:
0.812 inches
Overall Width:
Between 0.270 inches and 0.290 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
0.063 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.234 inches and 0.266 inches
Body Height:
Between 0.297 inches and 0.328 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
7.50 inch-ounces
Center To Center Distance Between Terminals:
Between 0.690 inches and 0.710 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.990 inches and 1.010 inches
Mounting Facility Quantity:
2
Terminal Location:

Lower adjacent side single row

NSN 5905-00-660-9962

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
0.10 watt at 95 degrees c
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0