NSN 5905-00-661-0591

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-661-0591

-20.0/+20.0 Electrical Resistance: 6.800 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:
6.800 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
3.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Style Designator: Axial terminal each end Shelf Life: N/a
Axial terminal each end Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0