NSN 5905-00-665-4899



View C	Online at https://aerobasegroup.com/nsn/5905-00-665-4899
Section	on Quantity:
1	
Body	Style:
Cylind	rical bushing mounted
Reliab	ility Indicator:
Not es	tablished
Overa	II Length:
Betwe	en 1.312 inches and 1.562 inches
Body	Diameter:
Betwe	en 1.032 inches and 1.156 inches
Shaft	Diameter:
Betwe	en 0.248 inches and 0.251 inches
Shaft	Length:
Betwe	en 0.844 inches and 0.906 inches
Mount	ting Bushing Length:
Betwe	en 0.344 inches and 0.390 inches
Body	Length:
Betwe	en 0.468 inches and 0.656 inches
Overa	Il Diameter:
1.515	inches
Shaft	Style:
Round	l, slotted
Actua	tor Type:
Single	shaft
Maxim	num Starting Torque:
6.00 ir	nch-ounces
Maxim	num Stop Torque:
128.00) inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-665-4899

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
150.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No