NSN 5905-00-665-5382

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-665-5382 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.125 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.969 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.969 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 220.0 kilohms all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 6 tab, solder lug

Shelf Life: N/a

NSN 5905-00-665-5382

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0