

View Online at <https://aerobasegroup.com/nsn/5905-00-665-6130>

Section Quantity:

2

Reliability Indicator:

Not established

First Flat Length:

0.438 inches

Flat Height:

0.218 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Shaft Style:

Round, flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

40.000 ohms 2nd section

Power Dissipation Rating Per Section In Watts:

25.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 15.0 2nd section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

Any acceptable

Switch Current Type And Rating In Amps:

5.000 ac/dc

Standard Taper Curve Per Section:

A 1st section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0