

View Online at <https://aerobasegroup.com/nsn/5905-00-665-7099>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

4.812 inches

Body Diameter:

1.880 inches

Shaft Diameter:

0.250 inches

Shaft Length:

2.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.750 inches

Overall Diameter:

1.880 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Maximum Starting Torque:

40.00 inch-ounces

Maximum Stop Torque:

240.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

12.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0