NSN 5905-00-665-7518

Section Quantity:

A single section

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-665-7518

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.438 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
200.000 ohms single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Standard Taper Curve Per Section:

NSN 5905-00-665-7518

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type	And	Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0