## NSN 5905-00-665-8657

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-665-8657 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.344 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.438 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.234 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 10.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

## NSN 5905-00-665-8657

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



		• -					
ш	ın	18 1	r 1+	Me	20	ıır	Δ.
u	,,,	IL	v.	IAIC	as	uı	┖.

--

Demilitarization:

No

Fiig:

A002a0