Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-665-9099

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.281 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

### 0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

**Screw Thread Series Designator:** 

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Locking bushing

## Features Provided:

Nonmetallic shaft

## **Electrical Resistance Per Section:**

10.000 kilohms single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0