NSN 5905-00-666-1057

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-666-1057 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.812 inches First Flat Length: 0.375 inches Flat Height: 0.216 inches **Body Diameter:** 1.780 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.812 inches **Overall Diameter:** 2.190 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

25.000 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

NSN 5905-00-666-1057

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	l olerance Per	Section	In Percen
-10.0 to 10.0	all sections		

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0