

View Online at <https://aerobasegroup.com/nsn/5905-00-666-1153>

**Section Quantity:**

1

**Body Style:**

Cylindrical studs mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

3.093 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

Between 0.688 inches and 0.750 inches

**Body Length:**

1.313 inches

**Mounting Hole/stud Circle Diameter:**

1.750 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

250.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Shaft Runout:**

0.003 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

250.0

**Function Conformity Tolerance Per Section:**

-0.20/+0.20 single section

**Power Dissipation Rating Per Section In Watts:**

2.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0