NSN 5905-00-666-1176

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-666-1176 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3125 inches Pilot Length: 0.0620 inches First Flat Length: 0.312 inches Flat Height: 0.187 inches **Undercut Diameter:** 1.422 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.718 inches **Body Length:** 0.992 inches **Mounting Lip Diameter:** 1.4530 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:**

0.60 inch-ounces

0.40 inch-ounces

Maximum Running Torque:

NSN 5905-00-666-1176

Shaft End Play: 0.00500 inches Shaft Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.001 inches
Lateral Runout:
0.004 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.004 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
500.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 solder stud
Shelf Life:
N/a

NSN 5905-00-666-1176

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0