NSN 5905-00-666-1199

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-666-1199 **Section Quantity: Body Style:** Cylindrical bushing mounted **Overall Length:** 3.156 inches **Body Diameter:** Between 1.657 inches and 1.719 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 2.375 inches **Body Length:** Between 0.750 inches and 0.812 inches **Overall Diameter:** 2.140 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.516 inches and 0.547 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Features Provided:

Nonmetallic shaft

NSN 5905-00-666-1199

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel in Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
0.375 in long bushing
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0