NSN 5905-00-666-1205

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



Se	ction Quantity:
1	
Во	dy Style:
Cyl	indrical bushing mounted
Re	liability Indicator:
No	t established
Ov	erall Length:
1.0	62 inches
Во	dy Diameter:
1.0	62 inches
Sh	aft Diameter:
0.2	50 inches
Sh	aft Length:
0.5	00 inches
Мо	unting Bushing Length:
0.3	75 inches
Во	dy Length:
0.5	62 inches
Sh	aft Style:
Ro	und, slotted
Sh	aft Bearing Type:
Bea	aring
Ac	tuator Type:
Sin	gle shaft
No	nturn Device Location:
At :	3 oclock and at 9 oclock
No	nturn Device Radius:
	31 inches
Sc	rew Thread Diameter:
0.3	75 inches
Sc	rew Thread Series Designator:
Un	
Sc	rew Thready Qty Per Inch (tpi):
32.	
Мо	unting Method:
Sta	andard bushing
Ele	ectrical Resistance Per Section:
500	0.000 kilohms single section
Po	wer Dissipation Rating Per Section In Watts:
2.0	free air single section

Function Conformity Per Section:

Single section independent linearity

NSN 5905-00-666-1205

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:		
-20.0 to 20.0 single section		
Standard Taper Curve Per Section:		
C single section		
Terminal Type And Quantity:		
3 tab, solder lug		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		

Fiig: A002a0