Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-666-2350

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.445 inches

Body Length:

0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0